

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number  
**WO 2005/058569 A1**

(51) International Patent Classification<sup>7</sup>: **B29B 9/06**, 9/12,  
B65D 65/46, C08L 29/04, C08J 3/12

**WIEDEMANN, Ralf** [DE/DE]; Reckitt Benckiser Produktions GmbH, Benckiserplatz 1, 67059 Ludwigshafen (DE).

(21) International Application Number:  
PCT/GB2004/005273

(74) Agents: **BOWERS, Craig, M.** et al.; Reckitt Benckiser plc, Group Patents Department, Dansom Lane, Hull HU8 7DS (GB).

(22) International Filing Date:  
16 December 2004 (16.12.2004)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0329529.2 19 December 2003 (19.12.2003) GB

(71) Applicant (*for all designated States except MN, US*): **RECKITT BENCKISER N.V.** [NL/NL]; Kantoorgebouw De Appelaer, De Fruittuinen 2-12, NL-2132 NZ Hoofddorp (NL).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for MN only*): **RECKITT BENCKISER (UK) LIMITED** [GB/GB]; 103-105 Bath Road, Slough, Berkshire SL1 3UH (GB).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **AYATS, Francesc** [ES/ES]; Reckitt Benckiser (Espana) SL, C/ Mataro, 28, Granollers, E-08400 Barcelona (ES). **OEHMS, Diana** [DE/DE]; Reckitt Benckiser Produktions GmbH, Benckiserplatz 1, 67059 Ludwigshafen (DE). **ROY, Pavlinka** [DE/DE]; Reckitt Benckiser Produktions GmbH, Benckiserplatz 1, 67059 Ludwigshafen (DE). **SALVADOR, Jordi** [ES/ES]; Reckitt Benckiser (Espana) SL, C/ Mataro, 28, Granollers, E-08400 Barcelona (ES).

**Declaration under Rule 4.17:**

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: PROCESS FOR MAKING A PELLET

(57) Abstract: The invention comprises a shaping process for making pellets of a thermoplastic extrudable resin composition. The resin composition comprises a thermoplastic polymer, plasticiser and optionally further additives. The plasticiser comprises a component which is solid at room temperature. The process is run at a temperature above the melting point of the plasticiser and below the melting / plastification temperature of the thermoplastic polymer.



WO 2005/058569 A1

PROCESS FOR MAKING A PELLET

The present invention relates to a process for making pellets of a thermoplastic extrudable polymer.

5

Processes for making pellets of thermoplastic extrudable polymer are well known in the plastic industry. Typically the pellets are cylindrical and approximately 3mm in diameter and 3mm in length. The pellets are used in a wide range  
10 of plastic article manufacturing processes.

The pellet manufacturing process generally includes a plastification step. In this step the formulation to be pelletised is melted and fed into a twin screw extruder. This has  
15 been seen to be beneficial as the pellets produced have been found to comprise of a homogeneous blend of the pellet components due to effective mixing of all molten components in the extruder.

20 EP-A-0 415 357 describes the making of pellets comprising polyvinylalcohol (PVOH) by melt extrusion with the extrusion being carried out in the temperature range of 150-195°C.

Pelletising processes having a plastification step have several disadvantages associated therewith. The principle disadvantage is the requirement for heating, which means that  
25 the energy consumption of these processes is very high.

Furthermore these 'hot' processes are not suitable for polymers which are heat sensitive (such as PVOH) due to heat induced decomposition. Also these 'hot' processes give a heat  
30

history to the polymer which has been found to negatively influence properties of the polymer. In the case of PVOH this has been found to detrimentally affect the PVOH water solubility .

5

In other pelletising processes dry compaction of the pellet components is carried out at low temperature. Thus the disadvantages of the 'hot' processes are avoided.

10 WO-A-98/26911 describes a low temperature process for the manufacture of PVOH pellets. In the process the pellets components, in this case a mixture of powdered PVOH and various additives such as plasticisers is fed between two rollers and compressed into pellets. The PVOH component in  
15 the pellet blend is not melted in the process and so the issue of heat degradation is avoided.

Also GB-937 057 describes such a low temperature compression process. This follows initial mixing of the plasticiser and  
20 PVOH at an elevated temperature.

However, although this process (the cold compression process) eliminates the problem of heat induced decomposition of the polymer, the pellets produced suffer from other disadvantages.  
25

Most of the disadvantages stem from the inherent nature of the compaction process, more specifically the rollers and the powder feed thereto. It has been found to be very difficult to ensure that the powder feed is spread evenly  
30 across the rollers. This has the effect that control of the

size of the pellets is difficult and so the size of the pellets can vary significantly.

Furthermore significant dust formation is typical for this  
5 kind of process. Additionally the pellets are commonly friable having poor integrity and easily form dust from friction rubbing against each other, thus worsening the dust issue. Both of these issues are attributed to the poor spreading and roller compression technique.

10

Furthermore significant variability of the composition of the pellets and poor homogeneity of the pellets has also been observed. The issues are also believed to be associated with the poor powder distribution over the rollers.  
15 The problem of the variability of the pellet composition and the poor homogeneity of the pellets is exacerbated when the pellets are taken and used in a further processing step.

These kinds of pellets, wherein the thermoplastic polymer  
20 component of the pellets is PVOH, are used in the manufacture of water soluble PVOH pouches in extrusion / injection moulding processes. The pouches, as an example, are commonly used to contain a detergent composition for use in an automatic washing machine (laundry / dishwasher). In these  
25 applications is it vital that the pellets have high homogeneity to ensure that the pouches produced have good integrity to be stable in storage and have the expected water dissolution properties.

Pellets produced in a cold compaction process, as described above, often fail to meet the level of homogeneity required for the processing into the pouch format.

- 5 It is an object of the present invention to obviate / mitigate the problems outlined above.

According to the present invention there is provided a shaping process for making pellets of a thermoplastic extrudable  
10 resin composition comprising a thermoplastic polymer, plasticiser and optionally further additives, the plasticiser comprising a component which is solid at room temperature, wherein the process is run at a temperature above the melting point of the plasticiser and below the melting / plasti-  
15 fication temperature of the thermoplastic polymer.

The shaping process may comprise pressing, extrusion, calendaring and / or compaction. Most preferably the shaping process comprises extrusion.

20

The process of the present invention has been found to overcome the disadvantages associated with the prior art. Firstly as the process is operated at a temperature below the melting / plastification temperature of the thermoplastic polymer the process has been found to be extremely energy efficient. Furthermore the heat degradation of heat  
25 sensitive materials in the resin blend is dramatically reduced by the lowered process temperatures.

30 Additionally as the process operates above the melting point of the plasticiser (which is then allowed to cool to form

the solid pellet) the pellets have been found to have a very low friability. Thus the pellets have a much lower tendency to release dust upon friction rubbing.

5 Furthermore as the pellets are produced at a temperature above the melting point of the plasticiser component the pellets have been found to have excellent homogeneity. More specifically both the overall composition of each pellet and the distribution of the individual components within the  
10 pellets have been found to have an high level of predictability and low variance. This is especially important when the pellets are used in a further processing step such as a second extrusion process (e.g. injection moulding) for the manufacture of an article comprising the thermoplastic poly-  
15 mer.

Generally the components are delivered to the shaping equipment used in the process in particulate form.

20 It has been found that the particle size of the raw materials used to make the pellets should be small. This has been observed to ensure high homogeneity of the pellets. The particle size of the raw materials used preferably is below 2000µm, more preferably below 1200µm, more preferably below  
25 400µm and most preferably about 200µm.

Preferably the plasticiser is present in the composition with at least 5%, more preferably 10%, most preferably 15%.

30 Preferably the temperature of the material within the extruder does not exceed a temperature which is 10°C below

the melting / plastification temperature of the thermoplastic polymer at any time. More preferably it does not exceed 15°C, more preferably 30°C and most preferably 45°C below the melting / plastification temperature of the thermoplastic polymer. However, it is desired that the temperature of the material exceeds the ambient air temperature. Preferably the temperature of material within the extruder is at least 40°C, more preferably at least 45°C, and most preferably at least 50°C.

10

The plasticiser has to at least partially melt at the preferred operating temperature. The melting point of the plasticiser component is preferably at least 15°C, preferably at least 30°C and most preferably at least 45°C below the melting / plastification temperature of the thermoplastic polymer.

15

Preferably the plasticiser comprises a carbohydrate.

20 Carbohydrates are usually represented by the generalised formula  $C_x(H_2O)_y$ . The term herein also includes materials which are similar in nature like gluconic acids or amino sugars which cannot be fully represented by this formula. Other carbohydrate derivatives like sugar alcohols such as sorbitol, glucitol, mannitol, galactitol, dulcitol, xylitol, erythritol, isomaltutose and isomalt fall within this term.

25

Most preferred carbohydrates include the more thermally stable carbohydrates such as sorbitol, glucitol, mannitol, galactitol, dulcitol, xylitol, erythritol, isomaltutose and isomalt.

30

Other preferred plasticiser systems include solid fatty acid alkoxylates, fatty alcohol alkoxylates or polyalkylene glycols (such as long chain polyethylene glycol).

5

The plasticiser may comprise a further auxilliary component. Preferred auxilliary components include glycerin, ethylene glycol, propylene glycol, diethylene glycol, diproylene glycol, triethanol amine, diethanol amine and methyldiethyl  
10 amine.

Once the or each strand has issued from the extruder it may be permitted to cool under ambient conditions. Alternatively cooling may be assisted. One way in which this may  
15 be done is by employing a cooled metal belt onto which the or each strand issues. Another way in which this may be done is by using a cooled fluid, preferably cooled air, downstream of the extruder. Another way is by blowing a fluid, preferably air, across the or each strand. One or  
20 more of these methods may be used.

Preferably the or each strand is separated into pellets, during the manufacture.

25 The strands are separated into pellets preferably by cutting. However, other separation methods, for example twisting, are not ruled out. A method may be envisaged whereby the strand is twisted at intervals when still plastic, to form "sausages", which can be separated by breaking the connections, once they have become more brittle. Partial cutting or pressing or nipping or perforating (all such methods  
30



collectively called "scoring" herein) to form frangible separation webs, may also be employed, to form tablet precursors. Separation of the precursors to produce pellets may be effected during manufacture or by the consumer, manageable lengths being provided from which the consumer breaks or twists off pellets as required. A pellet precursor may be, for example, a straight row of pellets, to be broken off as needed.

10 The extrusion pressure may be whatever is required to carry out the process in an efficient manner. Suitably it is in excess of 3 bar (0.3MPa), preferably in excess of 5 bar (0.5MPa), and more preferably is preferably in excess of 8 bar (0.8MPa). More preferably still is preferably in excess of 12 bar (1.2MPa). Most preferably it is in excess of 40 bar (4MPa). The extrusion pressure preferably does not exceed 100 bar (10MPa), more preferably 60 bar (6MPa).

Generally the pellets are for use in injection moulding processes. The injection moulding process is preferably used for the manufacture of water soluble pouches intended to contain a detergent formulation for use in an automatic washing machine or in an automatic dishwasher. Thus the pellets preferably comprising a water-soluble / water-dispersible thermoplastic polymer

In this use the advantageous properties of the pellets produced in accordance with the invention, especially the high homogeneity have been found to be particularly beneficial. It is believed that this property is most beneficial as the integrity of the injection moulded product relies upon such

high homogeneity of the composition being injection moulded as otherwise the low homogeneity will be reflected in the injection moulded product. The high homogeneity has been found to lead to predictable water solubility of injection  
5 moulded products.

Preferably the water-soluble / water-dispersible thermoplastic polymer comprises PVOH or a derivative thereof.

10 Other water-soluble / water-dispersible polymers may be used in the process either as an alternative or in addition to PVOH. Preferred examples include poly(vinylpyrrolidone), poly(acrylic acid), poly(maleic acid), a cellulose derivative (such as a cellulose ether / hydroxypropyl methyl cel-  
15 lulose), poly(glycolide), poly(glycolic acid), poly(lactides), poly (lactic acid) and copolymers thereof.

Processing aids may be present in the admixture which is processed. Preferred processing aids include mono-, di-,  
20 tri-carboxylic acids / salts thereof, fatty acids such as stearic acid / salts thereof, mono-, di- or triglycerides / salts thereof, aerosil, inorganic and organic pigments.

The invention will now be illustrated with reference to the  
25 following non-limiting Examples.

Examples:Example 1:

- 5 The pelletising process was conducted on an extruder (twin screw, ICMA S. Giorgio, Milan (dedicated to processing of plastic blends and alloys)).

The extruder had the following characteristics.

10

Screw diameter: 35 mm

Screw length: 40 cm

Working pressure: 30 bar

Output: 5 kg/h.

- 15 Temperature zones: 6 (T1=50°C, T2=60°C, T3=T4=90°C, T5=105°C and T6 (the die) =105°C.)

The extruder was attached to a two-roll unit used as a cooling source and connected to a pellet cutter.

20

The following formula was fed into the extruder in powder form.

Material	%
PVOH resin	85.0
Sorbitol	11.0
Processing aids	4.0
Total	100.0

- 25 The pellets obtained were chilled to room temperature. The formula yielded solid pellets having low friability.

**Example 2:**

The pelletising process was conducted on a pellet press  
5 (model V3-75 from Universal Milling Technologies).

The press had the following characteristics.

Die diameter:	350 mm
10 Holes diameter:	2 mm
Hole length:	3 mm
Infeed cone:	45°
Space between die / rollers:	1.5 mm
Die speed:	5m/s
15 Motor:	30 kW
Temperature:	98-102°C

The following formulae were fed into the extruder in powder  
form.

20

Material	Formula 1	Formula 2	Formula 3
PVOH resin	81.0	87.0	85.0
Sorbitol	15.0	11.0	11.0
Processing aids	4.0	2.0	4.0
Total	100.0	100.0	100.0

The pellets obtained were chilled to room temperature. Each  
formula yielded solid pellets having low friability.

CLAIMS

1. A shaping process for making pellets of a thermoplastic extrudable resin composition comprising a thermoplastic  
5 polymer, plasticiser and optionally further additives, the plasticiser comprising a component which is solid at room temperature, wherein the process is run at a temperature above the melting point of the plasticiser and below the melting / plastification temperature of the thermoplastic  
10 polymer.
2. A process according to claim 1, wherein the process comprises pressing, extrusion, calendering and / or compaction.
- 15 3. A process according to claim 1 or 2, wherein the plasticiser is present in the composition in at least 5%, more preferably 10%, most preferably 15%.
4. A process according to claim 2 or 3, wherein the shaping  
20 process comprises extrusion.
5. A process according to claim 4, wherein the temperature of the material within the extruder does not exceed a temperature which is 10°C, more preferably 15°C, more preferably  
25 bly 30°C and most preferably 45°C below the melting / plastification temperature of the thermoplastic polymer at any time.
6. A process according to claim 4 or 5, wherein the temperature of material within the extruder is at least 40°C, more  
30 preferably at least 45°C, and most preferably at least 50°C.

7. A process according to any one of the proceeding claims, wherein the particle size of the raw materials used is below 2000 $\mu$ m, more preferably below 1200 $\mu$ m, more preferably below 400 $\mu$ m and most preferably about 200 $\mu$ m.

8. A process according to according to any one of claims 1 to 7, wherein the plasticiser comprises a carbohydrate.

9. A process according to claim 8, wherein the carbohydrate is selected from the group comprising gluconic acids, amino sugars, sugar alcohols such as sorbitol, glucitol, mannitol, galactitol, dulcitol, xylitol, erythritol, isomaltutose and isomalt.

15

10. A process according to claim 8, wherein the carbohydrate is selected from the group comprising sorbitol, glucitol, mannitol, galactitol, dulcitol, xylitol, erythritol, isomaltutose and isomalt.

20

11. A process according to any one of claims 1 to 10, wherein the thermoplastic polymer is water-soluble / water dispersible.

12. A process according to claims 11, wherein the thermoplastic polymer comprises PVOH or a derivative thereof.

13. A process according to any one of claims 1 to 12, wherein the thermoplastic polymer comprises poly(vinylpyrrolidone), poly(acrylic acid), poly(maleic acid), a cellulose derivative (such as a cellulose ether /

hydroxypropyl methyl cellulose), poly(glycolide), poly(glycolic acid), poly(lactides), poly (lactic acid) and copolymers thereof.

5 14. A process according to claim 12 or 13, wherein the pellets are for use in injection moulding processes.

15. A process according to any one of claims 12 to 14,  
wherein the injection moulding process is used for the manu-  
10 facture of water soluble pouches intended to contain a detergent formulation for use in an automatic washing machine or in an automatic dishwasher.

# INTERNATIONAL SEARCH REPORT

PCT/GB2004/005273

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B29B9/06 B29B9/12 B65D65/46 C08L29/04 C08J3/12

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B29B C08L C08J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>FR 2 831 478 A (MULTIBASE)  2 May 2003 (2003-05-02)  page 1, line 28 - line 37  page 3, line 24 - page 4, line 32  page 8, line 15 - line 19  page 15, line 15 - page 16, line 18  page 20, line 12 - page 21, line 36  page 23, line 31 - page 26, line 19  page 27, line 25 - page 28, line 3  page 33, line 16 - line 30  page 34, line 21 - line 33</p> <p style="text-align: center;">----- -/--</p>	1-15



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

4 April 2005

Date of mailing of the international search report

11/04/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Fageot, P



# INTERNATIONAL SEARCH REPORT

PCT/GB2004/005273

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>DE 28 41 238 A1 (HOECHST AG)  3 April 1980 (1980-04-03)  page 4, line 1 - line 7  page 6, line 4 - line 22  page 7, line 34 - page 8, line 26  page 9, line 5 - line 20  page 10, line 30 - page 11, line 9  -----</p>	1-14
A	<p>EP 0 466 057 A (AIR PRODUCTS AND  CHEMICALS, INC)  15 January 1992 (1992-01-15)  page 2, line 26 - line 30  page 2, line 56 - page 3, line 6  page 3, line 34 - line 43  page 4, line 13 - line 21  page 5, line 26 - line 34  page 6, line 1 - line 31  -----</p>	1-4, 8-12,14, 15

## INTERNATIONAL SEARCH REPORT

PCT/GB2004/005273

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2831478	A	02-05-2003	FR 2831478 A1	02-05-2003
			EP 1438175 A1	21-07-2004
			WO 03035363 A1	01-05-2003
DE 2841238	A1	03-04-1980	AT 366079 B	10-03-1982
			AT 207579 A	15-07-1981
			CA 1125446 A1	08-06-1982
			DE 2964688 D1	17-03-1983
			DK 118979 A	24-09-1979
			EP 0004587 A2	17-10-1979
			ES 478736 A1	01-06-1979
			FI 790964 A	24-09-1979
			JP 1497910 C	29-05-1989
			JP 54131654 A	12-10-1979
			JP 63043424 B	30-08-1988
			MX 150450 A	09-05-1984
			NO 790973 A	25-09-1979
			US 4323492 A	06-04-1982
			US 4542178 A	17-09-1985
EP 0466057	A	15-01-1992	US 5028648 A	02-07-1991
			AT 129730 T	15-11-1995
			CA 2046408 A1	13-01-1992
			DE 69114193 D1	07-12-1995
			DE 69114193 T2	04-04-1996
			EP 0466057 A1	15-01-1992
			FI 913374 A	13-01-1992
			JP 4226557 A	17-08-1992
			NZ 238870 A	23-12-1992